



05000ECB Motor Oil 0W-20 Premium Synthetic EcoBlue

Document version: May 6, 2024



Description

This Premium Synthetic 0W-20 engine oil is suitable for Ford EcoBlue diesel engines where the Ford M2C952-A1 approval is required. This motor oil has been developed for Ford, among others, and can also be used where an SAE 0W-20 with ACEA C6 specification is recommended. Due to the advanced additive package, this motor oil provides optimal protection against LSPI, and motor and cambelt (if it runs in oil) are optimally protected under all temperatures and driving conditions. Due to the exceptional cleaning properties, pollution in the exhaust gas after-treatment system and turbo is prevented. This engine oil has excellent fuel-saving properties.

According to the specifications of

ACEA C5, C6
API SN Plus / SP
Ford WSS-M2C952-A1
ILSAC GF-6A
Jaguar/Land Rover STJLR.03.5006
Opel/GM dexos™D

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|-----------|--------|----------------|------------------|
| 05001ECB | 1 L | 6 | 450 |
| 05005ECB | 5 L | 4 | 112 |
| 05020ECB | 20 L | 1 | 30 |
| 05060ECB | 60 L | 1 | 6 |
| 05205ECB | 205 L | 1 | 2 |
| 05999ECB | 1000 L | 1 | - |
| P05000ECB | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|-------|--------------------|------------|
| Density at 15°C | 0.843 | kg/l | ASTM D4052 |
| SAE | 0W-20 | | |
| Kinematic Viscosity at 40°C | 39.8 | mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 8.3 | mm ² /s | ASTM D445 |
| Viscosity Index | 191 | | ASTM D2270 |
| Flashpoint | 234 | °C | ASTM D92 |
| Pourpoint | -45 | °C | ASTM D97 |
| Total Base Number | 9.4 | mgKOH/g | ASTM D2896 |

These characteristics are typical of current production. Variations in these characteristics may occur.