



## 06000S Motor Oil 0W-40 High Performance Street

Document version: May 6, 2024



### Description

This premium synthetic high-grade motor oil has been specially developed for the latest generation of high performance engine performance. This motor oil ensures excellent protection against wear at high revolutions due to a superior lubrication film.

### According to the specifications of

ACEA A3/B4  
API SN  
BMW LL-01  
ILSAC GF-4  
MB-Approval 229.5  
Porsche A40  
Renault RN 0700 / RN 0710  
VW 502.00 / 505.00

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
06001S	1 L	6	450
06005S	5 L	4	112
06020S	20 L	1	30
06060S	60 L	1	6
06205S	205 L	1	2
06999S	1000 L	1	-
P06000S	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.844	kg/l	ASTM D4052
Viscosity	0W-40		
Kinematic Viscosity at 40°C	80.1	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	13.8	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	178		ASTM D2270
Dynamic Viscosity at -35°C	6040	mPa.s	ASTM D5293
Flashpoint COC	220	°C	ASTM D92
Pourpoint	-57	°C	ASTM D6892
Total Base Number	10.1	mgKOH/g	ASTM D2896
Sulphated Ash	1.09	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.