



18000M Gearbox Oil 75W-85 GL-5 Premium Synthetic FE

Document version: May 6, 2024



Description

This premium synthetic SAE 75W-85 fuel-saving transmission oil has been specially developed for various transmissions. This high grade transmission oil is used in the differential for the multitronic of the VAG group and where a SAE 75W-85 GL-5 is specified, among other things.

According to the specifications of

API GL-5
Alfa Romeo
BMW 83 22 0 396 706
Fiat 9.55550-DA8 / 9.55550-MX3 / 9.55550-MZ1 / 9.55550-MZ3
Lancia
MB 235.7
VW G 052 145 / 052 190 / 055 190
VW TL 52 145 / 52 190
ZF TE-ML 18

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
18001M	1 L	6	450
18020M	20 L	1	30
18060M	60 L	1	6
18205M	205 L	1	2
18999M	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density	0.87	kg/l
Viscosity	75W-85	
Kinematic Viscosity	12.1	mm ² /s
Viscosity Index	144	
Flashpoint	190	°C
Pourpoint	-51	°C
Brookfield Viscosity	55000	mPa.s

These characteristics are typical of current production. Variations in these characteristics may occur.