



37000 UTTO GL-4 Mineral

Document version: May 6, 2024



Description

This mineral GL-4 UTTO (Universal Tractor Transmission Oil) transmission oil has been specially developed for tractors that need one lubrication oil for the hydraulic system, drive, differential, wet brakes and clutches.

According to the specifications of

API GL-4
Allison C4
CASE IH MS 1206 / MS 1207 / MS 1210
CASE New Holland MAT 3505 / 3525
Ford New Holland FNHA-2-C-201.00 / M2C134-C / M2C134-D
John Deere J20C / J20D
Massey Ferguson M-1135 / M-1143 / M-1145
Volvo Construction Equipment WB-101
ZF TE-ML 03E / 05F / 17E / 21F

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 37001 | 1 L | 6 | 450 |
| 37005 | 5 L | 4 | 112 |
| 37020 | 20 L | 1 | 30 |
| 37060 | 60 L | 1 | 6 |
| 37205 | 205 L | 1 | 2 |
| 37999 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|--------|--------------------|--------|
| Density at 15°C | 0.885 | kg/l | |
| Viscosity | 10W-30 | | |
| SAE | 10 | | |
| Kinematic Viscosity at 40°C | 58.5 | mm ² /s | |
| Kinematic Viscosity at 100°C | 10 | mm ² /s | |
| Viscosity Index | 158 | | |
| Dynamic Viscosity at -20°C | 2900 | mPa.s | |
| Flashpoint COC | 212 | °C | |
| Pourpoint | -39 | °C | |
| Total Base Number | 7.5 | mgKOH/g | |

These characteristics are typical of current production. Variations in these characteristics may occur.