



# AD26000 Radiator Stop Leak and Conditioner

Document version: May 6, 2024



## Description

MPM Radiator Stop Leak and Conditioner is used to prevent and repairs leakages in the radiator, water pump and cylinder head.

### Main benefits

- Permanently and reliably seals/prevents hair line cracks and leakages.
- Lubricates the water pump.
- Eliminates the need of costly repairs.
- Protects the entire cooling system against rust and corrosion.
- Does not harm rubber hoses, plastics or metals such as copper and aluminium parts/gaskets.
- Is not poisonous and does not contain acids.

### Application

Suitable for all petrol, diesel and LPG engine cooling systems with radiators made of aluminium, plastic or steel.

Mixable with water, cooling fluids and conventional anti-freeze.

## Application manual

Shake well before use. Pour contents of 250 ml bottle into the cooling system of a warm engine (not hot) with the cabin heating switched 'on'. Keep the engine running for approximately 10 minutes or drive a short distance. The contents of one 250ml bottle is suitable to treat a cooling system holding up to 12 litres of coolant, antifreeze or water. Attention: Be careful whilst opening the radiator / cooling system hot coolant or steam may escape from the system.

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
AD26250	0.25 L	6	-

## Standard analyses

TEST	VALUE	METHOD
Shelf life	1	year(s)
Density at 20°C	1.02	kg/l
Colour	brown	
pH	6	
Odour	neutral	

These characteristics are typical of current production. Variations in these characteristics may occur.