



BL001000BIO Marine TC-W3 Oil 2-Stroke High Performance Biodegradable

Document version: May 6, 2024



Description

This marine TC-W3 Oil 2-stroke biolube is a full synthetic biodegradable 2-stroke oil for use in water-cooled outboard engines of watercrafts, jet skis and Evinrude E-TEC engines. This thermally stable oil ensures outstanding piston cleanliness and protection against rust.

The biodegradable 2-stroke oil is readily miscible with gasoline and suitable as self-mixing or in oil injection systems.

The mixing ratio of the oil is 2% (1:50) and 1% (1:100) in accordance with the recommendation with the engine manufacturer.

According to the specifications of

API TC+
CEC L-33-T-82 > 80%
NMMA TC-W3

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL001001BIO	1 L	6	450
BL001005BIO	5 L	4	112
BL001020BIO	20 L	1	30
BL001060BIO	60 L	1	6
BL001205BIO	205 L	1	2
BL001999BIO	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.897	kg/l	
Colour	green		
Kinematic Viscosity at 40°C	47	mm ² /s	
Kinematic Viscosity at 100°C	8.5	mm ² /s	
Viscosity Index	170		
Flashpoint COC	105	°C	
Pourpoint	-36	°C	
Total Base Number	9.6	mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.