



41000A Motor Oil SAE 10 Super Single Grade

Document version: May 6, 2024



Description

This mineral SAE 10 Super Single Grade oil has been developed for a wide range of purposes and is extremely suitable for stationary engines, for industrial transmissions and for hydraulic systems.

According to the specifications of

ACEA E2
API CF-4 / SG
Caterpillar TO-2
MAN 270
MB 227.0 / 228.0
MIL-L-2104E
MIL-L-46152E
ZF TE-ML 03B / 05K

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
41001A	1 L	6	450
41005A	5 L	4	112
41020A	20 L	1	30
41060A	60 L	1	6
41205A	205 L	1	2
41999A	1000 L	1	-
P41000A	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.875	kg/l	
Viscosity	10W		
Kinematic Viscosity at 40°C	41	mm ² /s	
Kinematic Viscosity at 100°C	6.7	mm ² /s	
Viscosity Index	118		
Flashpoint COC	212	°C	
Pourpoint	-39	°C	
Total Base Number	7.0	mgKOH/g	
Sulphated Ash	0.88	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.