



54000 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic

Document version: May 6, 2024



Description

MPM 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic Ester Technology is suitable for air- and water-cooled 4-stroke engines and gearboxes. This engine oil gives high performance protection to engines and gearboxes under heavy conditions due to the high-quality base oils with ester blend. The combination of exceptional anti-wear/friction additives and the lubricity of the mixture reduces oil consumption and extends engine life. This multi-grade SAE 10W-40 engine oil has been developed for motorcycles with or without wet clutches and is backwards compatible with API SG, SH, SJ, SL, and SM specifications.

According to the specifications of

API SN
JASO MA / MA2

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
54001	1 L	6	450
54004	4 L	4	112
54020	20 L	1	30
54060	60 L	1	6
54205	205 L	1	2
54999	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.854	kg/l	ASTM D4052
Colour	Red		VISUAL
Viscosity	10W-40		
Kinematic Viscosity at 40°C	95	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	14.9	mm ² /s	ASTM D445
Viscosity Index	165		ASTM D2270
Pourpoint	-45	°C	ASTM D6892
Total Base Number	7.3	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.