



## BL032000 Marine Engine Oil Multi Grade 15W-40

Document version: May 6, 2024



### Description

This universal mineral marine engine oil is specially suitable for use in the first generation normal duty petrol engines and diesel engines with or without turbocharged.

### According to the specifications of

API CG-4  
Allison C4  
Caterpillar TO-2  
Cummins  
DAF  
Deutz/MWM  
Lister  
MAN M 271  
MB-Approval 228.1  
Vetus  
Volvo VDS  
Yanmar

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL032001	1 L	6	450
BL032005	5 L	4	112
BL032020	20 L	1	30
BL032060	60 L	1	6
BL032205	205 L	1	2
BL032999	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.883	kg/l
Viscosity	15W-40	
SAE	15W-40	
Kinematic Viscosity at 40°C	107	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	14	mm <sup>2</sup> /s
Viscosity Index	132	
Flashpoint COC	228	°C
Pourpoint	-30	°C
Total Base Number	6.1	mgKOH/g
Sulphated Ash	1	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.